

Coaxial protection device for N connection: male/female




Coaxial data cable protection devices


- High pulsed current carrying capacity 2 x 2.5 kA (10/350)
- Simple mounting (adapter plug), m = plug/f = female connector
- Optimised transmission behaviour
- 5-year guarantee
- With N connector
- Including OBO M25 Quick clip for simple installation

Type	Con- nec- tion range system	Frequency range	Pack. pcs	Weight kg/100 pcs.	Item No.
DS-N M/W	N	0 - 3 GHz	1	12,200	5093996

Dimensions



Connection options



DS-N M/W

Maximum continuous voltage AC V	U_c	130
Maximum continuous voltage DC V	U_c	185
Category		Type 1+2 / D1+C2
Lightning protection zone LPZ		0-2
Number of poles		1
Rated current A	I_n	10
Wave resistance Ω	Z_c	50
Impulse durability wire-wire		C2: 10 kV / 5 kA (8/20 μ s)
Impulse durability wire-earth		C2: 10 kV / 5 kA (8/20 μ s)
Impulse discharge current (10/350) kA	I_{imp}	2,5
Total discharge current (8/20) kA		10
Total discharge current (10/350) kA		5
Protection level V		<800
Frequency range		0 - 3 GHz
Insertion loss dB	S_{21}	$\leq 0,62$
Return loss dB	S_{11}	≥ 14
Temperature range °C	ϑ	-40-80
Installation type		Connector/cable adapter
Connection type		N
Connection system		N
Protection rating		IP40
Shielding connection available		Yes
Shield connection		Direct
Testing standard		IEC 61643-21